



PRODUCT DESCRIPTION

StreetBond Sealer Concentrate is a high quality sealer that can be applied to the surface of a newly completed project to reduce dirt and tire pick up on StreetBond SB150, StreetBond SB120 Pavement Coating, or StreetBond Premium System in hot climates. It can also be used on the surface to create a semi-gloss finish to StreetBond SB150 and StreetBond SB120 Pavement Coating coatings that some customers find aesthetically appealing. For aesthetic applications, reapplication may be needed in regular intervals to maintain shiny appearance.

WARRANTY

See applicable warranties for complete coverage and restrictions.

PACKAGING & SHELF LIFE

One unit (box) of StreetBond Sealer Concentrate consists of:

Two 1.58 gallon (6.0 liter) jugs

Shelf life is 24 months if unopened containers are stored between 40°F and 90°F (4°C and 32°C).

RECOMMENDED USES

- Reduce dirt and tire pick up in hot climates
- Create a semi-gloss finish over StreetBond Pavement Coatings

PRODUCT CHARACTERISTICS

STREETBOND SEALER CONCENTRATE	
Description	Milky liquid
Density	8.5 lb/gal (1.01 g/mL) [ASTM D1475]
Volume Solids	21% [ASTM D2697]
Weight Solids	22% [ASTM D2369]
VOC (calculated)	<100 g/L
Freeze Point	32°F (0°C)

Friction BPN (Sealer over SB150)	Dry = 61, Wet = 54 [ASTM E303]
Friction BPN (Premium System)	Dry = 114, Wet = 97 [ASTM E303]
Drying Time (Touch Dry)	1-4 hours at 77°F (25°C) and 40% humidity [ASTM D5895]

APPLICATION INSTRUCTIONS

Mixing: Dilute StreetBond Sealer Concentrate in a 1:1 ratio with water and mix thoroughly for 2 minutes. A small amount of StreetBond Colorant can be added during mixing to reduce sheen and improve color matching.

Surface Preparation: If using on coating that has been recently applied, verify coating is completely dry to the touch before applying sealer. For light colored surfaces, wait at least 1 hour after the coating is dry to the touch before applying sealer. If using on an aged project, ensure the surface is clean by using a backpack blower or compressed air to remove dust, debris, and surface contaminants. If water is used to clean the surface, ensure that the surface is completely dry prior to applying StreetBond Sealer Concentrate.

Recommended Application: Using a low pressure handheld or backpack sprayer, spray sealer onto desired area. Use a soft bristle broom or roller to even out the surface coverage. On textured surfaces, be sure to remove excess Sealer from the grout lines and distribute coating evenly to ensure a continuous membrane is formed. StreetBond Sealer Concentrate is milky white when sprayed, but dries clear with a semi-gloss sheen.

COVERAGE RATES	
Application Rate	300 sq ft/gal (7.4 m ² /l)
One Mixed Unit (2 jugs)	Covers approx. 2,000 ft ² (186m ²), depending on surface texture.

Coating must be allowed to cure before introducing traffic. Cure time may vary based on climate conditions and ranges between 6–24 hours.

LIMITATIONS & PRECAUTIONS

No precipitation should be expected within 24 hours. Do not ship or store unless protection from freezing is available.

SAFETY & HANDLING

For specific information regarding safe handling of this material please refer to the Safety Data Sheet (SDS).

CLEAN UP

Thoroughly rinse application equipment with clean water.