



StreetBond® Acrylic Textured White Line Paint

Technical Data Sheet

StreetBond® Acrylic Textured White Line Paint is an extremely durable, 100% acrylic emulsion fortified with fine silica. StreetBond® Acrylic Textured White Line Paint is specially formulated for use on many indoor and outdoor athletic and recreational surfaces. StreetBond® Acrylic Textured White Line Paint offers neat, clean, long-lasting line markings. StreetBond® Acrylic Textured White Line Paint is designed to be applied over all other StreetBond® Acrylic surfaces or uncoated asphalt surfaces. StreetBond® Acrylic Textured White Line Paint is not for use on untreated concrete surfaces

PRODUCT INFORMATION

| Product Characteristics | Test Method | Data |
|-----------------------------------|-------------|-----------------|
| VOC | calculated | 100 g/L maximum |
| Rotational Viscosity, 77F, 20 RPM | Brookfield | 23,000 ± 5000 |
| Density, lb/gal | ASTM 1475 | 11.7 ± 0.5 |
| pH | - | 8.5 to 9.5 |

Uses

StreetBond® Acrylic Textured White Line Paint is used for Line and Event markings for sport courts including, but not limited to, basketball, hockey/in-line skating, pickleball, playground, running surface, shuffleboard, tennis and multi-purpose courts. StreetBond® Acrylic Textured White Line Paint is part of the StreetBond® Sport Court System that may include resurfacer, filler, finish and line striping.

Limitations & Precautions

- Do not apply StreetBond® Acrylic Textured White Line Paint when the surface temperature is below 50 °F (10 °C) or when surface temperature is above 130 °F (55 °C).
- Do not apply when rain, fog or high humidity is imminent.

Packaging & Storage

5 gallon pails (18.9 L)
1 gallon pails (3.7 L)

Storage: Store unopened containers between 40°F and 90°F (4°C and 32°C). Do not store in direct sunlight.

Application Instructions

StreetBond® Acrylic Textured White Line Paint is to be applied over surfaces which have already received StreetBond® Acrylic coatings or uncoated asphalt surfaces. New asphalt pavement shall cure a minimum of 14 days before applying StreetBond®. Not for use on untreated concrete surfaces. The surface must be clean and free of grease, oil and any other foreign material. StreetBond® Acrylic Textured White Line Paint is applied with a paint brush, roller or other suitable paint application equipment. Clean equipment with water immediately after use.

- Approximately one-gallon StreetBond® Acrylic Textured White Line Paint is required for a standard double's tennis court. 500 lin. ft. @ 2" wide, per gallon (1 gal. generally required for one double's tennis court, 481 in. ft. with 2 in. wide lines). Uncoated asphalt surfaces may require two coats when striping. Do not apply over coal tar emulsions.

PRODUCT INFORMATION

Safety & Handling

For specific information regarding safe handling of this material, please refer to the Safety Data Sheet (SDS).

Cleanup

Thoroughly rinse application equipment with clean water before it dries.